



SPECIFICATION SHEET
05SBHC24SSD

DESCRIPTION:
5" STAINLESS STEEL SLOTTED GRATE

WRITTEN SPECIFICATION:

Grating shall be 05SBHC24SSD heavy duty ADA compliant and heel proof slotted grate. The grate shall be made of grade T304 stainless steel per ASTM A-240. The grate surface shall have a bead blast finish. The grate shall be 4.875" wide x 24" long x 0.75" thick and have a minimum load rating of DIN Class D (exceeds H-20/HS-25).

PRODUCT DATA

MATERIAL:	T304 STAINLESS STEEL
FINISH:	BEAD BLAST
ADA COMPLIANT:	YES
HEEL PROOF:	YES
LOCKING DEVICE:	CLIPLOCK
WEIGHT (LB):	13.7
OPEN AREA (IN²/LF):	10.7





LOAD RATINGS

DIN / EN1433:	CLASS D
AASHTO:	EXCEEDS M-306, H-20, & HS-25
ASME:	EXTRA HEAVY DUTY
FAA:	NO
LOAD CAPACITY:	1,856 PSI

PHONE: 770-505-6575	MODEL BY: JDP
296 INDUSTRIAL BLVD. N. DALLAS, GA 30132 222 WEST 33RD ST. OGDEN, UT 84401 13300 RAMBLEWOOD DR. CHESTER, VA 23836	DRAWING BY: KM
	REVIEWED BY: JDP
	DATE: 08/22/2025
	SCALE: 1 : 3
	REV # : 3

WWW.DURATRENCH.COM

- NOTES
- GRATES MAY BE MANUFACTURED TO REQUIRED RADII
 - ADA COMPLIANCE DEPENDENT UPON DIRECTION OF TRAVEL



TOLERANCES
FRACTIONAL = ± 1/8"
ANGULAR = ± 1°