



SPECIFICATION SHEET
05SEHS24SPA

DESCRIPTION:
5" STAINLESS PERFORATED GRATE

WRITTEN SPECIFICATION:

Grating shall be 05SEHS24SPA heel proof and ADA compliant stainless steel perforated grate. The perforations shall be no more than 1/4" diameter making the grate heel proof and compliant with the requirements of the Americans with Disabilities Act handbook section 4.5.4. The grate shall be made of 12 ga T304 stainless steel per ASTM A-240. The grate shall be 4.875" wide x 24" long x 0.75" thick and have a minimum load rating of DIN Class A.

PRODUCT DATA

MATERIAL:	T304 STAINLESS STEEL
FINISH:	ELECTROPOLISHED
ADA COMPLIANT:	YES
HEEL PROOF:	YES
LOCKING DEVICE:	CLIPLOCK
WEIGHT (LB):	4.1
OPEN AREA (IN²/LF):	9.3



LOAD RATINGS

DIN / EN1433:	CLASS A
AASHTO:	NO
ASME:	NO
FAA:	NO
LOAD CAPACITY:	70 PSI


PHONE: 770-505-6575	MODEL BY:	LRC
296 INDUSTRIAL BLVD. N. DALLAS, GA 30132 222 WEST 33RD ST. OGDEN, UT 84401 13300 RAMBLEWOOD DR. CHESTER, VA 23836	DRAWING BY:	EV
	REVIEWED BY:	LRC
	DATE:	02/01/2024
	SCALE:	1 : 3
	REV # :	IC-0

WWW.DURATRENCH.COM


NOTES
1. GRATES MAY BE MANUFACTURED TO REQUIRED RADII



TOP VIEW



SIDE VIEW



END VIEW

TOLERANCES
.X = ±0.1
.XX = ±0.04
.XXX = ±0.004
FRACTIONAL = ± 1/16"
ANGULAR = ± 0.5°