



SPECIFICATION SHEET
08SBHF24SSF

DESCRIPTION:
8" SLOTTED STAINLESS STEEL GRATE

WRITTEN SPECIFICATION:

Grating shall be 08SBHF24SSF slotted grate. The grate shall be fabricated of T304 stainless steel. The grate shall have a bead blast finish. The grate shall be 8" wide x 24" long x 2 1/4" thick with 1 1/2" grate seat height and have a minimum load rating of DIN Class F (exceeds H-20/HS-25).

PRODUCT DATA

MATERIAL:	T304 STAINLESS STEEL
FINISH:	BEAD BLAST
ADA COMPLIANT:	YES
HEEL PROOF:	YES
LOCKING DEVICE:	CLIPLOCK
WEIGHT (LB):	42.4
OPEN AREA (IN²/LF):	17.9


LOAD RATINGS

DIN / EN1433:	CLASS F
AASHTO:	EXCEEDS M-306, H-20, & HS-25
ASME:	EXTRA HEAVY DUTY
FAA:	YES
LOAD CAPACITY:	4,244 PSI

PHONE: 770-505-6575	MODEL BY:	LRC
296 INDUSTRIAL BLVD. N. DALLAS, GA 30132 222 WEST 33RD ST. OGDEN, UT 84401 13300 RAMBLEWOOD DR. CHESTER, VA 23836	DRAWING BY:	EV
	REVIEWED BY:	LRC
	DATE:	07/16/2024
	SCALE:	1 : 3.5
	REV # :	IC-0

WWW.DURATRENCH.COM

- NOTES
1. GRATES MAY BE MANUFACTURED TO REQUIRED RADII
 2. ADA COMPLIANCE DEPENDS ON DIRECTION OF TRAVEL



TOLERANCES
.X = ±0.1
.XX = ±0.04
.XXX = ±0.004
FRACTIONAL = ± 1/16"
ANGULAR = ± 0.5°