



SPECIFICATION SHEET
10SBAC24DGD

DESCRIPTION:
10" GALVANIZED DUCTILE IRON SLOTTED GRATE

WRITTEN SPECIFICATION:

Grating shall be 10SBAC24DGD slotted grate. The grate shall be made of grade 80-55-06 cast ductile iron conforming to ASTM A536-84. The grate shall have a hot dip galvanized finish. The grate shall be 10" wide x 24" long x 1 1/2" thick and have a minimum load rating of DIN Class D (exceeds H-20/HS-25).

PRODUCT DATA

MATERIAL:	DUCTILE IRON 80-55-06
FINISH:	HOT DIP GALVANIZED
ADA COMPLIANT:	YES
HEEL PROOF:	NO
LOCKING DEVICE:	CLIPLOCK
WEIGHT (LB):	30.6
OPEN AREA (IN²/LF):	34.1


LOAD RATINGS

DIN / EN1433:	DIN CLASS D
AASHTO:	EXCEEDS M-306, H-20 & HS-25
ASME:	EXTRA HEAVY DUTY
FAA:	NO
LOAD CAPACITY:	1,258 PSI


PHONE: 770-505-6575	MODEL BY: JDP
296 INDUSTRIAL BLVD. N. DALLAS, GA 30132	DRAWING BY: EV
222 WEST 33RD ST. OGDEN, UT 84401	REVIEWED BY: JDP
13300 RAMBLEWOOD DR. CHESTER, VA 23836	DATE: 05/21/2025
	SCALE: 1 : 4
	REV # : 1

WWW.DURATRENCH.COM


- NOTES**
1. GRATES MAY BE MANUFACTURED TO REQUIRED RADII
 2. ADA COMPLIANCE DEPENDENT UPON DIRECTION OF TRAVEL




ISOMETRIC VIEW



TOP VIEW



SIDE VIEW



END VIEW

TOLERANCES
FRACTIONAL = ± 1/8"
ANGULAR = ± 1°