



SPECIFICATION SHEET  
14SGLR24SS2

DESCRIPTION: 14" WIDE STAINLESS STEEL  
BAR GRATE

WRITTEN SPECIFICATION:

Grating shall be 14SGLR24SS2 bar grating. Grates shall be load banded. Grate shall be fabricated from T304 stainless steel per ASTM-A240 with bead blast finish. The grate shall be 14" wide x 23 15/16" long x 1 1/2" thick with 3/16" thk. bearing bars at 1 3/16" o.c. and 4" o.c. cross bars. Grates shall have a minimum load rating of DIN Class B (exceeds H-20).

PRODUCT DATA


MATERIAL:	T304 STAINLESS STEEL
FINISH:	BEAD BLAST
ADA COMPLIANT:	NO
HEEL PROOF:	NO
LOCKING DEVICE:	SADDLE CLIP
WEIGHT (LB):	28.4
OPEN AREA (IN²/LF):	126.2

LOAD RATINGS


DIN / EN1433:	CLASS B
AASHTO:	EXCEEDS H-20
ASME:	LIGHT DUTY
FAA:	NO
LOAD CAPACITY:	369 PSI

PHONE: 770-505-6575	MODEL BY: JDP
296 INDUSTRIAL BLVD. N. DALLAS, GA 30132  222 WEST 33RD ST. OGDEN, UT 84401  13300 RAMBLEWOOD DR. CHESTER, VA 23836	DRAWING BY: KM
	REVIEWED BY: JDP
	DATE: 12/16/2024
	SCALE: 1 : 5
	REV # : IC-0


WWW.DURATRENCH.COM




ISOMETRIC VIEW



TOP VIEW



SIDE VIEW



END VIEW

TOLERANCES

.X = ±0.1  
.XX = ±0.04  
.XXX = ±0.004  
FRACTIONAL = ± 1/16"  
ANGULAR = ± 0.5°