



**SPECIFICATION SHEET**  
**38SATC24DBD**

DESCRIPTION:  
**38" DUCTILE IRON SOLID COVER**


WRITTEN SPECIFICATION:

Cover shall be 38SATC24DBD solid cover. The cover shall be made of grade 80-55-06 cast ductile iron conforming to ASTM A 536-84. The grate shall be E-coated black. The cover shall be 38" wide x 24" long x 4" thick (with 1 1/2" grate seat height) and have a minimum load rating of DIN Class D (exceeds H-20/HS-25).


PRODUCT DATA	
MATERIAL:	DUCTILE IRON 80-55-06
FINISH:	E-COATED BLACK
ADA COMPLIANT:	YES
HEEL PROOF:	YES
LOCKING DEVICE:	CLIPLOCK
WEIGHT (LB):	291.3
OPEN AREA (IN²/LF)	N / A
LOAD RATINGS	
DIN / EN1433:	DIN CLASS D
AASHTO:	EXCEEDS M-306, H-20, & HS-25
ASME:	EXTRA HEAVY DUTY
FAA:	NO
LOAD CAPACITY:	1,182 PSI
PHONE: 770-505-6575	MODEL BY: JDP
296 INDUSTRIAL BLVD. N. DALLAS, GA 30132  222 WEST 33RD ST. OGDEN, UT 84401  13300 RAMBLEWOOD DR. CHESTER, VA 23836	DRAWING BY: EV
	REVIEWED BY: JDP
	DATE: 08/11/2025
	SCALE: 1 : 7.5
REV # : 1	

[WWW.DURATRENCH.COM](http://WWW.DURATRENCH.COM)


NOTES  
1. GRATES MAY BE MANUFACTURED TO REQUIRED RADII




TOP VIEW



ISOMETRIC VIEW



SIDE VIEW



END VIEW

TOLERANCES  
FRACTIONAL = ± 1/8"  
ANGULAR = ± 1°